

LED TAIL LIGHTS

(1994-2001 1500)

(1994-2002 2500 / 3500)

INSTALLATION INSTRUCTIONS

CONTENTS

- (1) LH Tail Light
- (1) RH Tail Light
- (2) Resistor Brackets
- (4) Vampire Clips
- (4) Phillips Bolts
- (4) Lock Nuts

TOOLS REQUIRED

- Phillips Screwdriver
- Pliers
- T-25 Screwdriver

1. Lower the vehicle tailgate. Locate and remove (2) T-25 screws from the tail light assembly. Firmly pull the tail light away from the vehicle to dislodge the (2) mounts from the vehicle bed.

Note: Verify the rubber mounts remained in the bed. If the rubber mounts are stuck to the tail light posts, remove the rubber and re-install into the bed mounting holes.

2. Remove the light bulb sockets from the original housing. Remove the brake/turn signal bulb from the socket. The original reverse light bulb will be reused.
3. Secure the tail light resistor to the included mounting bracket using the included (2) Phillips bolts and (2) lock nuts. The vampire clips will be used to secure the resistor to the inside of the vehicle bed.
4. Fit the reverse light bulb & socket into the tail light housing. Plug in the bulb connector into the brake/turn signal light socket.
Note: The brake/turn signal connector is directional/polarized. Test lighting functionality on both sides of the vehicle before re-installing the tail light into the vehicle bed.
5. Press the tail light to the vehicle bed, ensuring the tail light seats into the rubber mounts. Secure into place using the original (2) T-25 screws.
6. Repeat Steps 1-5 for the remaining tail light assembly.

Installation is now complete.