

# Installation Instructions

## WARRANTY

GTS products are guaranteed to be free of manufacturing defects for materials and workmanship. This lifetime warranty is limited to the original purchaser under conditions of normal usage and applies to all G.T. Styling products, which have been properly installed per provided instructions. Examples of defects may include: material imperfections, warping or fit problems at installation. Damages due to vandalism, misuse, neglect, improper installation, scratches or road hazards, (such as: impact, road debris or breakage due to improper consumer handling), are not covered. Seller's and manufacturer's only obligations shall be to replace the product proved to be defective. Labor charges, injuries or any other loss or damages whatsoever, including those incurred in installation, paint or painting of GTS products, repair or replacement, as well as incidental damages are excluded. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use or the inability to use the product. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be changed except by an agreement signed by officers of the seller and manufacturer.

To conform with Federal and some States laws, some GTS products are intended for show, competition and off road use only.

# Installation Instructions



## Headlight Covers

---

### IMPORTANT:

- **PLEASE READ INSTRUCTIONS COMPLETELY BEFORE INSTALLING**
  - **CAUTION** – Ensure covers are properly secured to vehicle before driving
    - Do not use automatic car washes with brushes
  - Clean with mild soap or plastic cleaner only. Solvents may scratch or fog the plastic.
    - Periodically check that all components are secure
- (In some cases, Headlight Covers are intended for show, competition and/or off-road use only)
- 

### COMPONENTS:

Headlight Covers  
Mounting Hardware: Varies by part  
Alcohol Wipe Pads  
GTS Logos

---

### PREP BEFORE INSTALLATION:

- A trial fit is recommended to ensure a proper fit
  - Wash and dry your headlight assembly with mild soap to remove any dirt and/or debris
  - Clean mounting areas with provided alcohol pads to remove any polish or wax
    - Painter's tape may be used to protect the vehicles paint, if necessary
- 

#### Method #1: Friction (Snap-on) Fit

1. Insert tab between light trim assembly and lower light trim.
2. Tilt cover upward.
3. Clip top of cover over the headlight assembly.
4. Some installations may not have a top clip and require even pressure to be applied so the part slides all the way back and is firmly adhering to the light.

#### Method #2: Dual-Lock

1. Mark and clean the location where the Dual-Lock aligns with the headlight opening.
2. Remove liner from dual-lock strips/circles.
3. Adhere dual-locks and press on the cover to ensure cover is secure.
4. Allow adhesive to cure for 48 hours. Do NOT wash or expose vehicle to extreme conditions during this time.
5. Use caution when installing and removing covers.

#### Method #3: Bracket-Type

1. Mark and clean the locations of the brackets.
2. Remove adhesive liner and attach it to the headlight opening with the face of the bracket even with the headlight opening.
3. When the adhesive has cured (48 hours), the cover can be installed by inserting the indentation into one bracket and flexing the cover to allow the other side to be inserted.