

# LED TAIL LIGHTS

(1999-2002 SILVERADO)

---

## INSTALLATION INSTRUCTIONS

### CONTENTS

---

- (1) LH Tail Light
- (1) RH Tail Light
- (2) Resistor Brackets
- (4) Vampire Clips
- (4) Phillips Bolts
- (4) Lock Nuts

### TOOLS REQUIRED

---

- Phillips Screwdriver
- Pliers

1. Lower the vehicle tailgate. Locate and remove (2) Phillips screws from the tail light assembly. Pull the tail light towards the rear of the vehicle to remove the tail light from the bed.
2. Remove the light bulb sockets from the original housing by pressing the socket tab while turning counter-clockwise.
3. Secure the tail light resistor to the included mounting bracket using the included (2) Phillips bolts and (2) lock nuts. The vampire clips will be used to secure the resistor to the inside of the vehicle bed.
4. Plug in the bulb connectors into the vehicle light sockets.  
**Note: The LED tail light bulb connectors are directional/polarized. Test lighting functionality on both sides of the vehicle before re-installing the tail lights into the vehicle bed.**
5. Fit the reverse light bulb and socket into the new tail light.
6. Press the tail light to the vehicle bed and secure into place using the original (2) Phillips screws.
7. Repeat Steps 1-5 for the remaining tail light assembly.

Installation is now complete.