

## V2 LED SIDE MIRROR MARKER LIGHTS

(2008-2016 F-250 / F-350)

INSTALLATION INSTRUCTIONS

## **CONTENTS**

- (1) LH Mirror Light
- (1) RH Mirror Light

## **TOOLS REQUIRED**

Small Flathead Screwdriver





STEP 1

Adjust the mirror upwards to gain access to the light mounting tab inside of the mirror. Using a small flathead screwdriver, press the tab towards the light and pull the light assembly outwards from the mirror.



STEP 2

 $Twist\ each\ bulb\ socket\ counter-clockwise\ to\ remove\ the\ light\ bulb\ socket\ from\ the\ light\ housing.$ 

Remove each light bulb from the light socket.





STEP 3

Identify the LH/RH light assembly using the embossed label in the lens/housing ("L" & "R").

Connect the bulb-style connectors on the light to the vehicle light bulb sockets. The connectors must be inserted the same as shown above. If accidently connected opposite, Fuse # 13, 14, or 40 in the vehicle interior fuse block may blow. Ensure Black(-) on chassis goes to Black(-) on the light.

Test turn signal and parking lamps for functionality.



STEP 4

Neatly route the wire leads into the light housing, and twist the light bulb sockets into the light assembly.





STEP 5

Align and press the light assembly into the mirror until the latch audibly clicks into place.

Re-adjust the mirror glass the desired position.



STEP 6

Repeat steps 1-5 for the remaining mirror light.

Installation is now complete.