WARRIOR WINCHES

SAMURAI WINCH OWNERS MANUAL

WINCH MODELS:

800VS12-CAD, 800VA12-CAD, 95DVA12-CAD 100VS12-CAD, 100VA12-CAD, 125VS12-CAD 125VA12-CAD, 145VS12-CAD, 145VA12-CAD **ENGLISH**

Register your product online









Doc-rev 20240521

SAVE THESE INSTRUCTIONS. This manual contains important safety precautions which should be read and understood before operating the product. Failure to do so could result in serious injury. Specifications, descriptions and images in this manual are as accurate as known at the time of publication, but are subject to change without notice.

WINCH MANUAL INTRODUCTION

INTRODUCTION

Congratulations on your purchase of a winch. We design and build winches to strict specifications and with proper use and maintenance your winch should bring you years of satisfying service.

Every effort has been made to ensure the accuracy and completeness of the information in this manual at the time of publication, and we reserve the right to change, alter and/or improve the product and this document at any time without prior notice.

SAFETY DEFINITIONS

Your winch can develop tremendous pulling forces and if used unsafely or improperly could result in property damage, serious injury or death. Throughout this manual, you will find the following symbols for caution, warning and danger. Pay particular attention to the notes preceded by these symbols as they are written for your safety. Ultimately, safe operation of this device rests with you, the operator.

⚠ DANGER

DANGER indicates a hazardous situation which, if not avoided, will result in death or serious injury.

№ WARNING

WARNING indicates a hazardous situation which, if not avoided, could result in death or serious injury.

⚠ CAUTION

CAUTION indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.

□ NOTICE

NOTICE indicates information considered important, but not hazard-related (e.g., messages relating to property damage).

GETTING TO KNOW YOUR WINCH

Your winch is a powerful piece of machinery. It is important that you understand the basics of its operation and specifications so that when you need to use it, you can use it with confidence and safety. Below is a list of the components of your winch and their uses.

- 1. This winch is engineered for maximum line pull with only one layer of cable spooled onto the winch drum (the first layer).
- Motor: The motor is powered by a 12-volt battery and provides power to the gear assembly which turns the drum and winds the wire rope in a direction.
- 3. Winch Drum: The winch drum is the cylinder on which the wire rope is stored. It can be spooled In or Out by use of the remote lead switch.
- 4. Winch Rope: Your winch been supplied with galvanized aircraft steel cable or synthetic rope and is designed specifically for load capacity of the rated line pull of this winch. The cable feeds on from underneath the drum position, it is looped at one end to accept the hook.
- 5. Fairlead (Supplied with selective models): For when using the winch at an angle the roller fairlead acts to guide the rope onto the drum evenly and minimizes damage to the rope or winch from abrasion.
- 6. Gear Assembly System: The reduction gears convert the winch motor power into extreme pulling forces.
- 7. Braking System: Braking action is automatically applied to the winch when the winch motor is stopped or there is a load on the wire rope. This is achieved by a separate external mechanical brake which applies the braking action. (Brakes are NOT designed as securing devices and the winch cables should never be left attached when vehicle / equipment is in transport).
- 8. Free Spooling Clutch: The clutch allows the operator to manually disengage ("CLUTCH OUT") the spooling drum from the gear train. This is called free spool. Engaging the clutch ("CLUTCH IN") locks the winch into the gear system.
- Solenoid: Power from the vehicle battery flows through the weatherproof switch before being directed to the winch motor.
- 10. Wired Remote lead Switch: The remote switch leads have a dual switch for powering in or powering out your winch drum. The remote control allows you to stand clear of the wire rope when the winch is under load.
- 11. Wireless remote (Supplied on selective models): This is designed and offered for 'Offroad' or 'None Commercial' use only and is not included in any warranty offered, This allows the operator to always control the winch from up to 50 Ft away.
- 12. Universal Flat Bed Mounting Channel: (Optional) Your winch could have been optionally supplied with a flat bed mounting channel that can be mounted to most flat surfaces such as trailers, truck beds and structures etc. The mounting channel also has a number of mounting holes and holes to accept your roller fairlead.
- 13. Pulley/Snatch Block: (Optional) If your winch is supplied with a pulley/snatch block which can double the pulling power of the winch, or change the pulling direction without damaging the wire rope. We recommend you to use a double line and snatch block for pulling over 70% of the rated line pull.

IMPORTANT SAFETY INSTRUCTIONS

⚠ DANGER

DO NOT EXCEED RATED CAPACITY.

INTERMITTENT USE ONLY - COOL BETWEEN USES.

DO NOT use winch for lifting/moving people or live animals.

A minimum of five wraps of cable around the drum barrel is necessary for pulling and holding the rated load. The cable clamp is not designed to hold the load without the 5 wraps of cable around the drum. (usually marked red on the drum end of the cable)

⚠ DANGER

Keep yourself and others a SAFE DISTANCE to the side of the cable when under tension.

NEVER stand or step over a cable, or near a cable under load using a winch blanket or sail is strongly recommended.

DON'T move the vehicle to pull a load (towing) on the winch cable. This could result in cable breakage.

Disconnect the remote control and isolate when not in use.

⚠ DANGER

DO NOT exceed maximum pull rating. Avoid "shock loading" by using the remote lead switch intermittently to take up the slack in the wire rope. "Shock loading" can far exceed the rated capacity for the wire rope and drum and will result in damaging winch and brake. By doing so will void any warranty.

♠ DANGER

DO NOT use you winch as securing device it is not designed for this and will result in damaging winch and brake and will void any warranty.

DO NOT exceed maximum line pull ratings shown on the tables.

DO NOT use as a hoist. Do not use for overhead lifting.

A DANGER

NEVER cut, weld, or modify any part of the winch or cable. By doing so will void any warranty

⚠ DANGER

When re-spooling the cable Ensure that the cable spools in the under-wind position with the cable entering the drum from the bottom, not the top. To re-spool correctly, and while wearing gloves, keep a slight tension on the cable while pushing the remote control button to draw in the cable. Walk toward the winch **NEVER** allowing the winch cable to slide through your fingers or hands.

DO NOT let your hands get within 12"(30cm) of the winch while respooling. Turn off the winch and repeat the procedure until a few feet of cable is left. Disconnect the remote control and finish spooling by hand by rotating the drum manually with the clutch disengaged. Keep hands clear of the fairlead and drum while the winch is under power.

⚠ DANGER

Failure to read and understand these warnings may result in personal injury and/or property damage.

Always use gloves to protect hands when handling any type or cable/rope. Never let the cable slide through your hands.

NEVER connect the cable back to itself.

Always apply blocks/chocks/straps to the wheels of the vehicle/ equipment when on an incline and in transportation.

No modifications, alterations, or deviation to the winch are authorized by the manufacturer and MUST NOT be made. By doing so will void any warranty.

Duration of winching pulls should be kept as short as possible. If the motor becomes uncomfortably hot to the touch, stop winching immediately and let it cool down for approx 8 mins minutes. Do not winch for more than two minutes at or near the maximum rated load without resting for 8 minutes.

⚠ DANGER

If the motor stalls **DO NOT** maintain winching. Winches are designed and made for intermittent use and should be used in conjunction with their duty cycles.

NEVER release the free-spool clutch when there is a load on the winch as the load will roll backwards.

Use hand saver hook when handling the hook for spooling or unspooling the wire rope.

NOTICE

The winch and its all-derivative types are rated at rated capacity when spooling the first rope layer on the drum. Overloading can damage the winch / motor / or wire rope.

For loads over 70% of rated line pull, we recommend the use of the pulley block / snatch block to double the wire rope line and reduce the strain. This will aid in two ways:

It will reduce the number of rope layers on the drum and reduce the load on the wire rope by as much as 50%. When doubling the lineback to the vehicle, always attach to the frame or another load bearing point..

○ NOTICE

The vehicle engine should always be kept running during winching operation to minimize battery drain and maximize power and speed of the winch. If the winch is used for a considerable amount of time with the engine switched off the battery will drain and be too weak to restart the vehicle engine. If this happens stop winching immediately, jump start the vehicle and charge the battery up before resuming winching operation.

○ NOTICE

Get to know your winch before you need to use it. We recommend that you set up a few test runs to familiarize yourself with rigging techniques; the sounds your winch makes under various loads and the way the cable spools on the drum, etc.

INSPECT the wire rope and equipment before each use. A frayed or damaged rope must be replaced immediately. Use only manufacturer's identical replacement rope with the exact specifications. (Ropes are not covered by any warranty offered)

INSPECT the winch installation and bolts to ensure that all bolts are tight before each operation or periodcally.

○ NOTICE

Store the remote control lead inside your vehicle or in a safe place.

Never connect the winch cable back to itself. This will cause cable to damage. Always use a pulley, snatch block, sling or chain of suitable strength as shown in the illustrations.

○ NOTICE

Any winch that appears to be faulty, damaged, worn, or operates abnormally MUST BE REMOVED FROM SERVICE UNTIL REPAIRED, REPLACED OR OVERHAULED. It is recommended that the necessary repairs ARE made by a manufacturer's authorized repair facility ONLY.

○ NOTICE

Pull only on areas of the vehicle as specified by the vehicle manufacturer.

 Only accessories, attachments and/or adapters supplied by the manufacturer shall be used.

⚠ CAUTION

When using the tool, basic safety precautions should always be followed to reduce the risk of personal injury and damage to the equipment. Read all these instructions before using this tool!

⚠ WARNING

Keep children away. Children must never be allowed in the work area, Do not let them handle machines, tools, extension cords or operate this tool.

⚠ WARNING

Store idle equipment. When not in use, tools must be stored in a dry location to inhibit rust. Always lock up tools and keep out of reach of children.

∴ CAUTION

Dress properly. Do not wear loose clothing or jewelry as they can be caught in moving parts. Protective, electrically non-conductive clothes and non-skid footwear are recommended when working. Wear restrictive hair covering to contain long hair.

№ WARNING

Use eye and ear protection. Always wear impact safety goggles. Wear a full-face shield if you are producing metal filings or wood chips. Wear a dust mask or respirator when working around metal, wood, and chemical dusts, and mists.

⚠ CAUTION

Maintain this winch with care. Keep this tool dry and clean for better and safer performance. Follow instructions for lubricating and changing accessories. Inspect winch rope periodically and, if damaged, have them replaced immediately by an authorized technician. The handles must be kept clean, dry, and free from oil and grease always.

Disconnect or unplug remote switch when not in use.

⚠ DANGER

Stay alert, watch what you are doing, use common sense. Do not operate any tool when you are tired.

WARNING

Check for damaged parts. Before using this winch, any parts that appear worn or damaged should be carefully checked to determine that it will operate properly and perform to its intended function. Check for damage including alignments, binding of moving parts; mounting fixtures. Any part that is damaged should be properly repaired or replaced by a qualified person. Do not use the tool if any switch does not turn "On" and "Off" properly.

№ WARNING

Replacement parts and accessories. When repairing or servicing, only use identical replacement parts. The use of any other parts will void the warranty.

№ WARNING

Do not operate tool if under the influence of alcohol or drugs.

Read warning labels on prescription to determine if your judgment or reflexes are impaired while taking drugs. If there is any doubt, do not operate the tool.

A DANGER

Keep hands and body away from Fairlead (cable intake slot) when operating.

Always secure vehicle in position before using winch.

↑ WARNING

Be certain the winch is properly bolted to a structure (or vehicle) that can hold the winches maximum rated load.

Do not use inappropriate attachments to extend the length of the winch cable.

⚠ DANGER

Never lift people or hoist loads over people or lift live animals.

Never come in between the winch and the load when operating.

№ WARNING

Do not apply any loads to the winch when cable is fully extended past the safety mark. Keep at least 5 full wraps of cable on the spool, (Usually marked red on the winch cable at the drum end.)

After moving any piece of equipment with the winch, secure the the equipment in place. Do not rely on the winch to hold for an extended period of time nor whilst in transport, winches are not securing device. By doing so will void any warranty

⚠ CAUTION

Examine winch before using. Components may be affected by exposure to chemicals, salts, and rust.

Do not cross over or go underneath winch cable when under load.

Use gloves while handling cable.

♠ WARNING

Never operate winch if cable shows any signs of weakening, such as knotting or kinking. If it does you must replace immediately.

∕ DANGER

Do not move your vehicle with the cable extended and attached to the load. You could easily exceed the winch rating and snap the cable.

When the vehicle is parked on an incline you should use wheel chocks.

⚠ CAUTION

Always re-spool cable neatly after any operation this will avoid any winch cable misalignment for the next use

⚠ CAUTION

The winch cable must be wound onto the drum under a load of at least 10% of the rated line pull or the outer wraps will draw into inner wraps and damage winch cable.

Before operating the winch under load you should check proper function of the winch by engaging and disengaging the clutch, by operating the directional controls, and operating the speed controls. This will ensure that the winch is working properly and will help prevent unintended damage and injury. Cycling the winch prior to loading will also ensure the gears are properly aligned.

⚠ CAUTION


Batteries contain gases which are flammable and explosive. Wear eye protection during installation and remove all jewelry. Do not lean over battery while making connections.

WARNING


It is **strongly recommended** a battery isolator is installed to protect vehicle, equipment and user from hazardous situations, if one isn't supplied it is recommended one is purchased and installed before operation of the winch.


Failure to install a battery isolator or safety cut off could result in damage to the vehicle, equipment and(or) operator and will result in voiding any warranty offered.


WINCH ASSEMBLY AND MOUNTING



- 1. Your winch is designed with a bolt pattern that is standard in this class of winch. Many winch mounting kits are available that utilize this bolt pattern for the most popular vehicle and mounting channels. If you cannot find a kit locally, contact us and we will provide you with the name of a dealer near you. If you utilize the mounting channel, you must ensure that it is mounted on a flat surface so that the three major sections (motor, drum and gear housing) are properly aligned. Proper alignment of the winch will allow even distribution of the full rated load and reduce the chance of damaging winch or equipment. Poor installation contributes to approx 90% equipment or winch damage.
- Start by connecting the Roller Fairlead to the Mounting Channel
 using 2 each of the Cap Bolt M10 X 35, Flat Washer, Lock Washer
 and securing with M10 Nut (Make sure the bolt is placed through the
 mounting channel and roller fairlead from inside the channel. This
 will allow enough clearance for the winch to be placed in the channel
 without obstruction.)
- 3. Assemble the winch to the (optional) Mounting Channel by first pulling and releasing the clutch knob to "Out" position (Free Spooling). Pull out a few inches of cable from the drum and feed the wire loop through the opening in the front of the mounting channel and roller fairlead. Now, using the remaining M10 x 35 Cap Bolts, Flat Washer, Lock Washer, and M10 Nut secure the winch to the mounting channel
- 4. Connect the battery and motor leads as the drawing above. Remember every type of winch is different.
- 5. Connect the winch motor as detailed below:







WINCH MANUAL RIGGING TECHNIQUES

CAUTION

Batteries contain gases which are flammable and explosive. Wear eye protection during installation and remove all jewelry. Do not lean over battery while making connections.

- 6. Assemble the Clevis Hook to the cable. Take off the pin from the Clevis Hook, connect the Clevis Hook to the cable and mount the pin back to the Clevis Hook.
- Always use the Hand Saver (Optional) when free-spooling and respooling the wire rope. Using the Hand Saver keeps your hands and fingers away from the rotating drum.
- 8. Check for proper drum rotation. Pull or turn the clutch knob to the "OUT" "Disengage" position (Free-spooling). Pull out some cable from the drum, and then turn the clutch knob to the "IN" "Engage" position to engage the gears. Press the cable out button on the remote lead switch. If the drum is turning and releasing cable, then your connections are accurate. If the drum is turning and collecting more cable, then reverse the leads on the motor. Repeat and check rotation.


RIGGING TECHNIQUES

Locate a suitable anchor such as a strong tree trunk or boulder.

ALWAYS use a sling or strap as an anchor point on a object, Never use the cable or hook as a anchor point attached to an object.


↑ CAUTION

NEVER attach the clevis hook back onto the winch cable as this could cause damage to the cable.



CAUTION

Do not winch from an acute angle as the wire rope will bind up on one side of the drum causing damage to wire rope (Bird Nesting) and cause major damage to winch and possible equipment.




○ NOTICE

Short pulls from an angle can be used to straighten the vehicle/ equipment. Long pulls should be done with the wire rope in a straight line to winch/vehicle, see above illustration.

⚠ CAUTION


When pulling a heavy load, place a blanket or jacket over the wire rope five or six feet from the hook because in the event of a broken cable it will dampen the force.

For additional protection open the hood/bonnet of the vehicle as shown.




□ NOTICE

For pulls over 70% rated line pull, we recommend the use of the snatch/pulley block to double line the wire rope. This reduces the load on the winch and the strain on the rope.



♠ DANGER

Never use your winch for overhead hoisting, lifting of people, moving people or moving of live animals.



WINCHING TECHNIQUES A-Z

- a. Take time to asses your situation and plan your pull.
- b. Put on gloves to protect your hands.
- c. Disengage the clutch where possible to allow free-spooling and also save battery power.
- d. (If supplied) Attach the hand saver hook to the clevis hook.
- e. Pull out the wire rope to your desired anchor point safely.
- f. Secure the clevis hook to the anchor point: Sling, chain or snatch block. Do not attach the hook back onto the wire rope.
- g. Engage the clutch.
- h. Connect the remote control lead to the winch.
- i. Start your engine to ensure power is being replenished to the vehicle battery.
- j. Power in the wire rope guiding the wire under tension to draw up the slack in the wire. Once the wire is under tension stand well clear. Never stand or step over the wire rope under tension.
- k. Double check your anchors and make sure all connections are secure.
- I. Inspect the wire rope. Make sure there are at least 5 wraps of wire rope around the winch drum.(usually marked with red)
- m. Drape a blanket or sail (Sold separately) over the wire rope approximately 5 to 6 feet from the hook. Open the hood/bonnet for added protection.
- n. Clear the area. Make sure all people, spectators are well back and that no one is directly in front or behind the vehicle or anchor point.
- o. Begin winching. Be sure that the wire rope is winding evenly and tightly around the drum. If needed, the vehicle that is being winched can be slowly driven to add assistance to the winching process. Avoid shock loading; keep the wire rope under tension.
- p. The vehicle to be winched should be placed in neutral and the emergency brake released. Only release the brake pedal when under full tension. Avoid shock loading to the winch. This can damage the winch, rope and vehicle.
- q. The winch is meant for intermittent use. Under full load with a single line rig do not power in for more than 8 minutes without letting the motor cool down for a few minutes and then resume the winching operation.
- r. The winching operation is complete once the vehicle is on stable ground and or can drive under its own power.

- s. Secure the vehicle. Be sure to set the brakes and place the vehicle in park.
- t. Release the tension on the wire rope. The winch is NOT designed as securing device and should NEVER hold a load or secure whilst in transport, winch cable MUST be released when equipment or vehicle is secure. Not doing so will possibly damage the brake and winch and void any warranty.
- u. Disconnect the wire rope from the anchor and NEVER leave connected.
- v. Rewind the wire rope. Make sure that any wire already on the drum has spooled tightly and neatly. If not, draw out the wire and re-spool from the point where the rope is tight.
- w. Keep your hands clear of the winch drum and fairlead as the wire rope is being drawn in.
- x. Secure the hook and hook strap.
- v. Disconnect the remote control lead and store in a clean, dry place.
- z. Clean and inspect connections and mounting hardware for next winching operation.

MAINTENANCE

- Periodically check the tightness of mounting bolts and electrical connections. Remove all dirt or corrosion and always keep clean.
- 2. Do not attempt to disassemble the gear box. Repairs should be done by the manufacturer or an authorized repair center.
- The gear box has been lubricated using a high temperature lithium grease and is sealed at the factory. No internal lubrication is required.

REPLACING THE WIRE ROPE

If the wire rope has become worn or is beginning to show signs of fraying, it must be replaced before being used again.

- 1. Turn the clutch to the "CLUTCH OUT" position.
- 2. Extend cable to its full length. Note how the existing cable is connected to the drum.
- Remove old cable assembly and attach new one as the old cable connected to the drum. Insert the end of the new rope and secure the screw M8x10.
- 4. Ensure that the new cable wraps in the same rotation direction as the old one. The cable should exit the drum from the bottom, under the drum. (Underwind).
- 5. Turn the clutch to the "CLUTCH IN" position.
- Winch cable onto drum, first five wraps being careful not to allow kinking, then winch cable must be wound onto the drum under a load of at least 10% rated line pull.

№ WARNING

Only replace the wire rope with the identical replacement part recommended by the manufacturer. Steel or synthetic ropes are NOT covered by any warranty offer and are sole responsibility of the owner or user to maintain and replace if necessary.

WINCH MANUAL TROUBLESHOOTING

TROUBLESHOOTING

Problem	Cause	Solution
	Remote assembly not connected properly	Check remote lead and connections.
	Loose battery cable connections	Check battery and connections.
	Defective remote assembly	Replace remote lead assembly.
Motor does not turn on	Defective motor	Check for voltage at armature port with Switch pressed. If no voltage is present, replace motor.
	Water has entered motor	Allow to drain and dry. Run winch until completely dry.
Motor runs but drum does not turn	Clutch not engaged	Turn clutch to the "In" position. If problem persists, ask a technician to check and repair.
Motor runs slowly or without normal power	Insufficient current or voltage	Operate winch while vehicle motor running
Motor overheating	Winch running for too long	Allow winch to cool down periodically.
Motor runs in one direction only	Loose or corroded battery cable or motor cable connections.	- Clean and tighten. -Repair or replace switch assembly.
Wingh hydring malfunction	Cable runs in wrong direction	Adjust the cable working direction
Winch braking malfunction	Brake slice worn or breakdown	Adjust braking angle or replaces with new brake slice

WINCH MANUAL WARRANTY*

WARRANTY*

BPE Solutions North America are the sole distributors of these WARRIOR WINCHES and associated brands/equipment.

BPE Solutions North America ("seller" or BPE) warrants to the original retail buyer only ("Buyer") that any mechanical component of this genuine winch ("product(s)") are free of defects in material and workmanship for the lifetime of the winch.

The electrical components (including the motor, contactor, and switches) will be free of defects in material and workmanship for a period of (3) three years (36 Months) from the original purchase provable date of purchase

Any product BPE Solutions North America determines to be defective will be repaired or replaced at our (BPE Solutions North America) sole discretion without charge to the Buyer upon Buyer's compliance with this procedure. Seller or its Authorized Agent may make reasonable charges for parts and(or) labour for repairs not covered by this Lifetime Limited Warranty. None warrantable returns will be charged at BPE Solutions North America standard rates. The warranties set forth herein are exclusive and in lieu of all other warranties, whether oral or written, express or implied.

If in the event your product becomes faulty within your warranty period

To obtain service or repair under this warranty, the Buyer shall mail, ship or otherwise deliver to the manufacturers address, at the Buyers expense; (1) the Product, (2) a written description of the problem, (3) Buyers name, address and contact number, (4) copy of the original purchase receipt or BPE Solutions North America can arrange a suitable collection method (Charges apply).

Warranty Exclusions

The Warranty does not cover the cost of labour or transportation/shipping charges for the replacement or installation of defective part(s).

This warranty does not apply to defects of the Product caused by; (1) normal wear and tear, (2) failure to comply with any installation, maintenance or subjecting the product to loads in excess of the loads written/listed in the owners manual or as detailed upon the Sellers website, (3) alteration or modification by any parties other than the manufacturer, (4) misuse, abuse, neglect, accidents, Acts of God, terrorism or (5) failure to correctly use the item according to the owners

manual (7) other causes beyond the control of the Seller after delivery of the Product to the Sellers Authorized Agent.

Other Exclusions

This Warranty does not cover steel cables, synthetic ropes, fairleads, wireless remotes or any exterior finishes outside thirty (30) Days from purchase.

BPE Solutions North America shall not be responsible or liable for any indirect or consequential damages. These consequential damages may include, but are not limited to, lost profits or loss of use, down time or damage to other person(s) equipment.

BPE Solutions North America reserves the right to change the Product design without notice. BPE Solutions North America reserves the right to replace any part or whole unit with a newer design of the same function.

SPECIFICATIONS 800VS12-CAD, 800VA12-CAD


Rated line pull	8000 lbs (3628kg)	
Gear reduction ratio	196:1	
Motor	12V:Input:5.8hp/4.3Kw Output: 2.7hp/2.0kW	
Overall dimensions	22"×6.3"×9.8" (559 mm ×160mm ×248mm)	
Drum size	Ø2.48 "×8.8 " (Ø63mm×223 mm)	
	Synthetic rope	Wire rope
Cable	Ø0.31" × 82 ' (Ø8mm × 25m)	Ø0.32" × 95 ' (Ø8.3mm × 29m)
Net Weight	800VA12-CAD	800VS12-CAD
iet weight	61.7 lbs (28kg)	85.9 lbs (39kg)

Line Pull, Line Speed and Amperes (First layer)

Line Pull lbs (kgs)	Line Speed ft/min (m/min)	Motor current Amps (Max) - 12V DC
0	36(11.0)	50
2000 (900)	17.4(5.3)	125
4000 (1800)	13.1(4.0)	200
6000 (2721)	10.5(3.2)	260
8000 (3628)	8.2(2.5)	310

Layer	Rated line pull lbs (kgs)	Total rope on the drum ft (m)
1	8000 (3628)	21.3 (6.5)
2	6620 (3000)	46.9 (14.3)
3	5650 (2562)	77.1 (23.5)
4	4920 (2230)	95.1 (29)

WINCH ASSEMBLY DRAWING 800VS12-CAD, 800VA12-CAD



WINCH PARTS LIST (800VS12-CAD, 800VA12-CAD)

#	Part Number	Description	Qty.
1	V950100	Motor Assembly	1
2	V800001	Cap Screw M10 x 35	6
3	V800002	Lock Washer Ф10	6
4	V800003	Think Flat Washer Ф10	6
5	V800004	Hex Flange Nut M10	6
6	V950200	Break / Shaft Assembly	1
7	V1200005	Bushing-Drum	2
8	V800006	Tie Bar	2
9	V800007	Screw M8 x 10	1
10	V800008	Think Flat Washer Ф8	4
11	V800009	Cap Screw M8 x 30	4
12	V1200300	Drum Assembly	1
13	V800010	Screw M5 x18	8
14	V800011	Lock Washer Ф5	8
15	V1200012	End Bearing	1
16	V800013	Gasket	1
17	V800014	Gear—Ring	1
18	V800400	Gear Carrier Assembly -(Output)	1
19	V800500	Gear Carrier Assembly (Intermediate)	1
20	V800600	Gear Carrier Assembly (Intput)	1
21	V800015	Gear—Input Sun	1
22	V800016	Trust Washer	1
23	V800017	Gear—Housing	1
24	V800018	Clutch Screw	1
25	V800019	Ring Seals	1
26	V800020	Clutch Cover	1
27	V1200021	Clutch	1
28	V800RS	Remote Control Switch(R8)	1
29	V800800	Cable Assembly	1
30	V80WRS	Wireless Remote Control Switch	1
31	V800900	Roller Fairlead	1
32	V800022	Mounting Play	1
33	V800023	Connecting Piece	1
34	V800024	Connecting Piece	1

#	Part Number	Description	Qty.
35	V801300	Wireless Switch Receiver	1
36	V1201400	Relay with Screw Assembly	1
37	V951500	Cover with Screw Assembly	1
38	V800025	Connecting Piece	1
39	V1200026	Connecting Block	4
40	V1200027	Connecting Rod Sets	2
41	V800028	Ring Seals	2
42	V800029	Six angle bar	1
43	V800030	Coupling	1
44	V800031	Coupling	1
45	V800032	Circlip For Hole	1
46	V800033	Bearing	1

SPECIFICATIONS 95DVA12-CAD


Rated line pull	9500 lbs (4309kg)	9500 lbs (4309kg)	
Gear reduction ratio	196:1		
Motor	12V:Input:6.1hp/4.6Kw Output:2.8hp/2.1kW	12V:Input:6.1hp/4.6Kw Output:2.8hp/2.1kW	
Overall dimensions	18"×6.3"×9.8" (456 mm ×160mm ×248mm)	18"×6.3"×9.8" (456 mm×160mm×248mm)	
Drum size	Ø2.48 "×4.7" (Ø63mm×120 mm)		
	Synthetic rope	Wire rope	
Cable	Ø0.37"×49.2 ' (Ø9.5mm×15m)	Ø0.36"×45.9 ' (Ø9.2mm×14m)	
Net Weight	Synthetic rope	Wire rope	
iet weignt	59.5 lbs (27kg)	70.5 (32kg)	

Line Pull, Line Speed and Amperes (First layer)

Line Pull Ibs (kgs)	Line Speed ft/min (m/min)	Motor current Amps (Max) - 12V DC
0	36 (11.0)	50
2000 (900)	17.4 (5.3)	120
3000 (1360)	15.4 (4.7)	150
6000 (2721)	10.5 (3.2)	260
8000 (3628)	8.2 (2.5)	300
9500 (4309)	6.5 (2.0)	355

Layer	Rated line pull lbs (kgs)	Total rope on the drum ft (m)
1	9500 (4309)	9.8(3.0)
2	7600 (3447)	24.6 (7.5)
3	6200 (2812)	42.7(13.0)
4	5400 (2449)	45.9 (14.0)

WINCH ASSEMBLY DRAWING 95DVA12-CAD



WINCH PARTS LIST (95DVA12-CAD)

# Part Number		Description	Qty.
1	V950100	Motor Assembly	1
2	V95SD0001	Cap Screw M10 x 35	6
3	V95SD0002	Lock Washer Ф10	6
4	V95SD0003	Think Flat Washer Ф10	6
5	V95SD0004	Hex Flange Nut M10	6
6	V950200	Break / Shaft Assembly	1
7	V1200005	Bushing-Drum	2
8	V95SD0006	Tie Bar	2
9	V95SD0007	Screw M8 x 10	1
10	V95SD0008	Think Flat Washer Ф8	4
11	V95SD0009	Cap Screw M8 x 30	4
12	V95SD0300	Drum Assembly	1
13	V95SD0010	Screw M5 x18	8
14	V95SD0011	Lock Washer Ф5	8
15	V1200012	End Bearing	1
16	V95SD0013	Gasket	1
17	V95SD0014	Gear-Ring	1
18	V95SD0400	Gear Carrier Assembly -(Output)	1
19	V95SD0500	Gear Carrier Assembly (Intermediate)	1
20	V95SD0600	Gear Carrier Assembly (Intput)	1
21	V95SD0015	Gear—Input Sun	1
22	V95SD0016	Trust Washer	1
23	V95SD0017	Gear-Housing	1
24	V95SD0018	Clutch Screw	1
25	V95SD0019	Ring Seals	1
26	V95SD0020	Clutch Cover	1
27	V1200021	Clutch	1
28	V95SDRS	Remote Control Switch(R8)	1
29	V95SD0800	Cable Assembly	1
30	V95SDWRS	Wireless Remote Control Switch	1
31	V95SD0900	Roller Fairlead	1
32	V95SD0022	Mounting Play	1
33	V95SD0023	Connecting Piece	1

#	Part Number	Description	Qty.
34	V95SD0024	Connecting Piece	1
35	V95SD1300	Wireless Switch Receiver	1
36	V1201400	Relay with Screw Assembly	1
37	V951500	Cover with Screw Assembly	1
38	V95SD0025	Connecting Piece	1
39	V1200026	Connecting Block	4
40	V95SD0027	Connecting Rod Sets	2
41	V95SD0028	Ring Seals	2
42	V95SD0029	Six angle bar	1
43	V95SD0030	Coupling	1
44	V95SD0031	Coupling	1
45	V95SD0032	Circlip For Hole	1
46	V95SD0033	Bearing	1

SPECIFICATIONS 100VS12-CAD, 100VA12-CAD


Rated line pull	10000 lbs (4500kg)	10000 lbs (4500kg)	
Gear reduction ratio	196:1		
Motor	12V:Input:6.1hp/4.6Kw Output:3.0hp/2.2kW		
Overall dimensions	22"×6.3"×9.8" (559 mm ×160mm ×248mm)	22"×6.3"×9.8" (559 mm ×160mm ×248mm)	
Drum size	Ø2.48 "×8.8" (Ø63mm×223 mm)	Ø2.48 "×8.8" (Ø63mm×223 mm)	
	Synthetic rope	Wire rope	
Cable	Ø0.37"×82' (Ø9.5mm×25m)	Ø0.36"×85.3 ' (Ø9.2mm×26m)	
Net Weight	100VA12-CAD	100VS12-CAD	
Net Weight	66.1 lbs (30kg)	88.1 lbs (40kg)	

Line Pull, Line Speed and Amperes (First layer)

Line Pull Ibs (kgs)	Line Speed ft/min (m/min)	Motor current Amps (Max) - 12V DC
0	36 (11.0)	50
2000 (900)	17.4 (5.3)	120
3000 (1360)	15.4 (4.7)	150
6000 (2721)	10.5 (3.2)	260
8000 (3628)	8.2 (2.5)	300
10000 lbs (4500)	5.9 (1.8)	365

Layer	Rated line pull lbs (kgs)	Total rope on the drum ft (m)
1	10000 (4500)	18 (5.5)
2	7600 (3447)	39.4 (12)
3	6200 (2812)	64 (19.5)
4	5400 (2449)	85 (26.0)

WINCH ASSEMBLY DRAWING 100VS12-CAD, 100VA12-CAD



WINCH PARTS LIST (100VS12-CAD, 100VA12-CAD)

#	Part Number	Description	Qty.
1	V950100	Motor Assembly	1
2	V950001	Cap Screw M10 x 35	6
3	V950002	Lock Washer Ф10	6
4	V950003	Think Flat Washer Ф10	6
5	V950004	Hex Flange Nut M10	6
6	V950200	Break / Shaft Assembly	1
7	V1200005	Bushing—Drum	2
8	V950006	Tie Bar	2
9	V950007	Screw M8 x 10	1
10	V950008	Think Flat Washer Φ8	4
11	V950009	Cap Screw M8 x 30	4
12	V1200300	Drum Assembly	1
13	V950010	Screw M5 x18	8
14	V950011	Lock Washer Φ5	8
15	V1200012	End Bearing	1
16	V950013	Gasket	1
17	V950014	Gear—Ring	1
18	V950400	Gear Carrier Assembly (Output)	1
19	V950500	Gear Carrier Assembly (Intermediate)	1
20	V950600	Gear Carrier Assembly (Input)	1
21	V950015	Gear—Input Sun	1
22	V950016	Trust Washer	1
23	V950017	Gear—Housing	1
24	V950018	Clutch Screw	1
25	V950019	Ring Seals	1
26	V950020	Clutch Cover	1
27	V1200021	Clutch	1
28	V950RS	Remote Control Switch (R8)	1
29	V950800	Cable Assembly	1
30	V95WRS	Wireless Remote Control Switch	1
31	V950900	Roller Fairlead	1
32	V950022	Mounting Play	1
33	V950023	Connecting Piece	1
34	V950024	Connecting Piece	1

#	Part Number	Description	Qty.
35	V951300	Wireless Switch Receiver	1
36	V1201400	Relay with Screw Assembly	1
37	V951500	Cover with Screw Assembly	1
38	V950025	Connecting Piece	1
39	V1200026	Connecting Block	4
40	V1200027	Connecting Rod Sets	2
41	V950028	Ring Seals	2
42	V950029	Six angle bar	1
43	V950030	Coupling	1
44	V950031	Coupling	1
45	V950032	Circlip For Hole	1
46	V950033	Bearing	1

SPECIFICATIONS 125VS12-CAD, 125VA12-CAD


Rated line pull	12500 lbs (5670kg)		
Gear reduction ratio	253:1		
Motor	12V:Input:6.7hp/5.0Kw Output:3.2hp/2.4kW		
Overall dimensions	22"×6.3"×9.8" (559 mm ×160mm ×248mm)	22"×6.3"×9.8" (559 mm ×160mm ×248mm)	
Drum size	Ø2.48 "×8.8 " (Ø63mm×223 mm)		
	Synthetic rope	Wire rope	
Cable	Ø0.43"×82 ' (Ø11mm×25m)	Ø0.4"×83.6 ' (Ø10.2mm×25.5m)	
Net Weight	125VA12-CAD	125VS12-CAD	
	70.5 lbs (32kg)	97 lbs (44kg)	

Line Pull, Line Speed and Amperes (First layer)

Line Pull Ibs (kgs)	Line Speed ft/min (m/min)	Motor current Amps (Max) - 12V DC
0	27.9 (8.5)	45
6000 (2721)	11.5 (3.5)	200
8000 (3628)	8.2 (2.5)	240
10000 (4535)	5.9 (1.8)	300
12500 (5670)	4.2(1.3)	380

Layer	Rated line pull lbs (kgs)	Total rope on the drum ft (m)
1	12500 (5670)	15.1 (4.6)
2	9533 (4324)	34.1 (10.4)
3	7907 (3586)	57.7 (17.6)
4	6755 (3064)	83.7 (25.5)

WINCH ASSEMBLY DRAWING 125VS12-CAD, 125VA12-CAD



WINCH PARTS LIST (125VS12-CAD, 125VA12-CAD)

#	Part Number	Description	Qty.
1	V1200100	Motor Assembly	1
2	V1200001	Cap Screw M10 x 35	6
3	V1200002	Lock Washer Ф10	6
4	V1200003	Think Flat Washer Ф10	6
5	V1200004	Hex Flange Nut M10	6
6	V1200200	Break / Shaft Assembly	1
7	V1200005	Bushing-Drum	2
8	V1200006	Tie Bar	2
9	V1200007	Screw M8 x 10	1
10	V1200008	Think Flat Washer Φ8	4
11	V1200009	Cap Screw M8 x 30	4
12	V1200300	Drum Assembly	1
13	V1200010	Screw M5 x18	8
14	V1200011	Lock Washer Ф5	8
15	V1200012	End Bearing	1
16	V1200013	Gasket	1
17	V1200014	Gear—Ring	1
18	V1200400	Gear Carrier Assembly (Output)	1
19	V1200500	Gear Carrier Assembly (Intermediate)	1
20	V1200600	Gear Carrier Assembly (Intput)	1
21	V1200015	Gear—Input Sun	1
22	V1200016	Trust Washer	1
23	V1200017	Gear—Housing	1
24	V1200018	Clutch Screw	1
25	V1200019	Ring Seals	1
26	V1200020	Clutch Cover	1
27	V1200021	Clutch	1
28	V120RS	Remote Control Switch (R8)	1
29	V1200800	Cable Assembly	1
30	V120WRS	Wireless Remote Control Switch	1
31	V1200900	Roller Fairlead	1
32	V1200022	Mounting Play	1
33	V1200023	Connecting Piece	1
34	V1200024	Connecting Piece	1

#	Part Number	Description	Qty.
35	V1201300	Wireless Switch Receiver	1
36	V1201400	Relay with Screw Assembly	1
37	V1201500	Cover with Screw Assembly	1
38	V1200025	Connecting Piece	1
39	V1200026	Connecting Block	4
40	V1200027	Connecting Rod Sets	2
41	V1200028	Ring Seals	2
42	V1200029	Six angle bar	1
43	V1200030	Coupling	1
44	V1200031	Coupling	1
45	V1200032	Circlip For Hole	1
46	V1200033	Bearing	1

SPECIFICATIONS 145VS12-CAD, 145VA12-CAD


Rated line pull	14500 lbs (6577kg)		
Gear reduction ratio	253:1		
Motor	12V:Input:7.2hp/5.4Kw Output:3.6hp/2.7kW		
Overall dimensions	23.35"×6.3"×9.8" (593 mm ×160mm ×248m	23.35"×6.3"×9.8" (593 mm ×160mm ×248mm)	
Drum size	Ø2.48 "×8.8 " (Ø63mm×223 mm)		
	Synthetic rope	Wire rope	
Cable	Ø11mm×25m (Ø0.43"×82 ')	Ø10.2mm×25.5m (Ø0.4"×83.6 ')	
Net Weight	145VA12-CAD	145VS12-CAD	
	72.7 lbs (33kg)	94.7 lbs (43kg)	

Line Pull, Line Speed and Amperes (First layer)

Line Pull Ibs (kgs)	Line Speed ft/min (m/min)	Motor current Amps (Max) - 12V DC
0	27.9 (8.5)	45
6000 (2721)	11.5 (3.5)	200
8000 (3628)	7.87 (2.4)	245
10000 (4535)	5.57 (1.7)	310
12000 (5443)	4.92 (1.5)	380
14500 (6577)	2.6 (0.8)	460

Layer	Rated line pull lbs (kgs)	Total rope on the drum ft (m)
1	14500 (6577)	15.1 (4.6)
2	11519 (5224)	34.1 (10.4)
3	9556 (4334)	57.7 (17.6)
4	8163 (3702)	83.7 (25.5)

WINCH ASSEMBLY DRAWING 145VS12-CAD, 145VA12-CAD



WINCH PARTS LIST (145VS12-CAD, 145VA12-CAD)

#	Part Number	Description	Qty.
1	V1450100	Motor Assembly	1
2	V1450001	Cap Screw M10 x 35	6
3	V1450002	Lock Washer Φ10	6
4	V1450003	Think Flat Washer Ф10	6
5	V1450004	Hex Flange Nut M10	6
6	V1450200	Break / Shaft Assembly	1
7	V1450005	Bushing—Drum	2
8	V1450006	Tie Bar	2
9	V1450007	Screw M8 x 10	1
10	V1450008	Think Flat Washer Φ8	4
11	V1450009	Cap Screw M8 x 30	4
12	V1450300	Drum Assembly	1
13	V1450010	Screw M5 x18	8
14	V1450011	Lock Washer Φ5	8
15	V1450012	End Bearing	1
16	V1450013	Gasket	1
17	V1450014	Gear-Ring	1
18	V1450400	Gear Carrier Assembly -(Output)	1
19	V1450500	Gear Carrier Assembly (Intermediate)	1
20	V1450600	Gear Carrier Assembly (Intput)	1
21	V1450015	Gear—Input Sun	1
22	V1450016	Trust Washer	1
23	V1450017	Gear—Housing	1
24	V1450018	Clutch Screw	1
25	V1450019	Ring Seals	1
26	V1450020	Clutch Cover	1
27	V1450021	Clutch	1
28	V145RS	Remote Control Switch(R8)	1
29	V1450800	Cable Assembly	1
30	V145WRS	Wireless Remote Control Switch	1
31	V1450900	Roller Fairlead	1
32	V1450022	Mounting Play	1
33	V1450023	Connecting Piece	1

#	Part Number	Description	Qty.
34	V1450024	Connecting Piece	1
35	V1451300	Wireless Switch Receiver	1
36	V1451400	Relay with Screw Assembly	1
37	V1451500	Cover with Screw Assembly	1
38	V1450025	Connecting Piece	1
39	V1450026	Connecting Block	4
40	V1450027	Connecting Rod Sets	2
41	V1450028	Ring Seals	2
42	V1450029	Six angle bar	1
43	V1450030	Coupling	1
44	V1450031	Coupling	1
45	V1450032	Circlip For Hole	1
46	V1450033	Bearing	1

