



CROSSBAR ROOF RACK

(2009-2014 F-150)

INSTALLATION INSTRUCTIONS

CONTENTS

- (2) Cross Bars
- (4) Cross Bar Mounts
- (4) 'L' Brackets
- (4) Bed Rail Nut Plates
- (8) M10x1.50 x 30mm Allen Bolts
- (8) M10 Lock Washers
- (8) M10 Flat Washers
- (8) M8x1.25 x 15mm Hex Bolts
- (8) M8 Lock Washers
- (8) M8 Flat Washers
- (8) M8 Nuts
- (4) Phillips Head Screws

TOOLS REQUIRED

- Phillips Screwdriver
- 14mm Wrench
- 6mm Allen Key

SKU # T565680

STEP 1

Secure the crossbar to the crossbar mounting bracket using (1) Phillips head screw.

Repeat this procedure for the remaining crossbar mounting brackets.

STEP 2

Secure the 'L' bracket to the crossbar mounting bracket using (2) M8x1.25 x 15mm hex bolts, (2) M8 lock washers, (2) M8 flat washers, and (2) M8 nuts.

Repeat this procedure for the remaining 'L' brackets. Do not fully tighten hardware to allow for adjustments later.

**STEP 3**

Place the crossbar assembly across the vehicle bed rails. Place (1) bed rail nut plate behind the 'L' bracket, then secure the crossbar assembly to the vehicle using (2) M10x1.50 x 30mm Allen bolts, (2) M10 lock washers, and (2) M10 flat washers.

Repeat this procedure for the remaining bed rail nut plates.

**STEP 4**

Tighten all hardware once the crossbars are in a suitable mounting location. Adjust the (2) Allen bolts per crossbar mounting bracket as necessary per application.

Installation is now complete.